

STEELPOINT 19FT – KNEELING AXLE TRAILER

K19H – HYDRAULIC
K19E – ELECTRIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

TRAILER SPECIFICATIONS

DECK SIZE	80" X 19', 102" Overall Width, 25'-3" Long		
DECK	10GA Steel Smooth Plate		
DECK HEIGHT	22" Empty, 20" loaded		
TIE DOWNS	16 Each "D" Rings		
AXLES	2 Each 7K Torsion Axles		
BRAKES	Hydraulic		
SUSPENSION	Torsion Axle		
TIRES AND WHEELS	ST235/85R16E		
TONGUE JACK	12K Drop Leg Side Wind		
HITCH	2-5/16" Ball, Optional 3" Pintle Eye		
LIGHTS	LED		
WIRING	Inside Conduits		
PLUG	7 Prong Flat RV		
SAFETY CHAIN	1/2" Grade 70		
STANDARD COLOR	Steelpoint Silver Frame. Deck Coated with Black Anti-Slip Surface		
SPARE TIRE WITH BRACKET	Standard		
FENDERS	Steel		
OPTIONS:	- 10K Electric Winch - Special Colors		
GVWR (LBS)	GAWR (LBS)	WEIGHT (LBS)	CAPACITY (LBS)
14250	2ea 7000	4245	10005

