

STEELPOINT 4X10 – LOW PROFILE TILT

T410H – HYDRAULIC T410E – ELECTRIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

TRAILER SPECIFICATIONS

DECK SIZE	75" Overall Width, 168" Long, 32" High		
BED SIZE	48" wide, 120" long		
DECK	1/8" Steel Diamond Plate with Expanded Metal Traction Strips		
DECK HEIGHT	16" High		
TIE DOWNS	"D" Rings		
STAKE POCKETS	4ea Stake Pockets		
AXLES	4.4k Torsion Axle		
BRAKES	Electric or Hydraulic		
SUSPENSION	Torsion Axle		
TIRES AND WHEELS	ST225/75R15D		
TONGUE JACK	7K Drop Leg		
HITCH	Standard 2" Ball, Optional 3" Pintle Eye		
LIGHTS	LED or Incandescent		
WIRING	Inside Conduit and Poly Loom		
PLUG	Standard 4 Prong Flat, Optional 7 Prong Flat RV		
SAFETY CHAIN	3/8" Grade 70		
STANDARD COLOR	Black Powder Coated, Other Colors Available		
TILTING MECHANISM	Manual tilt with single snubber cylinder to cushion tilting of deck		
SPARE TIRE WITH BRACKET	Standard		
FENDERS	Bolt on plastic or metal fenders		
TRACTION STRIPS	Deck mounted traction strips aid loading of small scissor lifts with small drive wheels		
OPSTIONS:	- Track Stop		
GVWR (LBS)	GAWR (LBS)	WEIGHT (LBS)	CAPACITY (LBS)
4,840	4,400	1,100	3,740

