

STEELPOINT 4X10 – LOW PROFILE TILT

T410H – HYDRAULIC T410E – ELECTRIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

TRAILER SPECIFICATIONS

DECK SIZE	75" Overall Width, 168" Long, 32" High
BED SIZE	48" wide, 120" long
DECK	1/8" Steel Diamond Plate with Expanded Metal Traction Strips
DECK HEIGHT	16" High
TIE DOWNS	4 Each "D" Rings
STAKE POCKETS	4ea Stake Pockets
AXLES	5.2k Torsion Axle
BRAKES	Electric or Hydraulic
SUSPENSION	Torsion Axle
TIRES AND WHEELS	ST225/75R15D
TONGUE JACK	7K Drop Leg
HITCH	Standard 2" Ball, Optional 3" Pintle Eye
LIGHTS	LED / Incandescent
WIRING	Inside Conduit and Poly Loom
PLUG	Standard 4 Prong Flat, Optional 7 Prong Flat RV
SAFETY CHAIN	3/8" Grade 70
STANDARD COLOR	Black Powder Coated, Other Colors Available
TILTING MECHANISM	Manual tilt with single snubber cylinder to cushion tilting of deck
SPARE TIRE WITH BRACKET	Standard
FENDERS	Bolt on plastic or metal fenders
TRACTION STRIPS	Deck mounted traction strips aid loading of small scissor lifts with small drive wheels
OPTIONS:	- Track Stop

GVWR (LBS)	GAWR (LBS)	WEIGHT (LBS)	CAPACITY (LBS)
5,720	5,200	1,320	4,400

