

STEELPOINT 4X12 – LOW PROFILE TILT

T412H – HYDRAULIC T412E – ELECTRIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

TRAILER SPECIFICATIONS

DECK SIZE	76" Overall Width, 192" Long, 34" High
BED SIZE	48" wide, 144" long
DECK	1/8" Steel Diamond Plate with Expanded Metal Traction Strips
DECK HEIGHT	18" High
TIE DOWNS	"D" Rings
STAKE POCKETS	4ea Stake Pockets
AXLES	7k Torsion Axle
BRAKES	Electric or Hydraulic
SUSPENSION	Torsion Axle
TIRES AND WHEELS	ST235/85R16E
TONGUE JACK	7K Drop Leg
HITCH	Standard 2-5/16" Ball, Optional 3" Pintle Eye
LIGHTS	LED
WIRING	Inside Conduits
PLUG	Standard 4 Prong Flat, Optional 7 Prong Flat RV
SAFETY CHAIN	3/8" Grade 70
STANDARD COLOR	Black Powder Coated, Other Colors Available
TILTING MECHANISM	Manual tilt with single snubber cylinder to cushion tilting of deck
SPARE TIRE WITH BRACKET	Standard
METAL FENDERS	Standard – Bolt On
TRACTION STRIPS	Deck mounted traction strips aid loading of small scissor lifts with small drive wheels
OPTIONS:	- Track Stop

GVWR (LBS)	GAWR (LBS)	WEIGHT (LBS)	CAPACITY (LBS)
7,700	7,000	1,902	5,798

