

STEELPOINT 5X10 – TANDEM AXLE

E510H – HYDRAULIC
E510E – ELECTRIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

TRAILER SPECIFICATIONS

DECK SIZE	61" Inside Fender, 90" Overall Width, 120" Long		
DECK	1/8" Steel Diamond Plate		
DECK HEIGHT	19 ½" Empty, 17 ½" loaded		
RAMPS	Spring Assisted Ramps		
TIE DOWNS	6 Each "D" Rings		
AXLES	4.4K Torsion Hydraulic Axles		
BRAKES	Hydraulic		
SUSPENSION	Torsion Axle		
TIRES AND WHEELS	ST225/75R15		
TONGUE JACK	7K Drop Leg Side Wind		
HITCH	Standard 2" Ball, Optional 3" Pintle Eye		
LIGHTS	LED		
WIRING	Inside Conduits		
PLUG	Standard 4 Prong Flat, Optional 7 Prong Flat RV		
SAFETY CHAIN	5/16" Grade 70		
STANDARD COLOR	Black Powder Coated, Other Colors Available		
SPRING ASSISTED RAMPS	Standard		
SPARE TIRE WITH BRACKET	Standard		
PLASTIC FENDERS	Standard		
OPTIONS:	- Track Stop		
GVWR (LBS)	GAWR (LBS)	WEIGHT (LBS)	CAPACITY (LBS)
8800	2ea 4400	1840	6960

