

STEELPOINT 6X14 – TANDEM AXLE

E614H – HYDRAULIC
E614E – ELECTRIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

TRAILER SPECIFICATIONS

DECK SIZE	70" Inside Fender, 101" Overall Width, 168" Long		
DECK	1/8" Steel Diamond Plate		
DECK HEIGHT	18" Empty, 16" loaded		
RAMPS	Spring Assisted Ramps		
TIE DOWNS	9 Each "D" Rings		
AXLES	6K Torsion Axle		
BRAKES	Electric or Hydraulic (See Pricing)		
SUSPENSION	Torsion Axle		
TIRES AND WHEELS	ST225/75R15D White Rim 6 on 5.5"		
TONGUE JACK	7K Drop Leg Side Wind		
HITCH	Standard 2-5/16" Ball, Optional 3" Pintle Eye		
LIGHTS	LED		
WIRING	Inside Conduits		
PLUG	Standard 4 Prong Flat, Optional 7 Prong Flat RV		
SAFETY CHAIN	3/8" Grade 70		
STANDARD COLOR	Black Powder Coated, Other Colors Available		
SPRING ASSISTED RAMPS	Standard		
SPARE TIRE WITH BRACKET	Standard		
PLASTIC FENDERS	Standard		
OPTIONS:	- Track Stop		

GVWR (LBS)	GAWR (LBS)	WEIGHT (LBS)	CAPACITY (LBS)
9990	2ea 6000	2614	7376

