

STEELPOINT 4X12 – LOW PROFILE TILT

T412H – HYDRAULIC T412E – ELECTRIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

TRAILER SPECIFICATIONS

| | | | |
|-------------------------|---|---------------------|-----------------------|
| DECK SIZE | 76" Overall Width, 192" Long, 34" High | | |
| BED SIZE | 48" wide, 144" long | | |
| DECK | 1/8" Steel Diamond Plate with Expanded Metal Traction Strips | | |
| DECK HEIGHT | 18" High | | |
| TIE DOWNS | 4 Each "D" Rings | | |
| STAKE POCKETS | 4 Each Stake Pockets | | |
| AXLES | 7k Torsion Axle | | |
| BRAKES | Electric / Hydraulic | | |
| SUSPENSION | Torsion Axle | | |
| TIRES AND WHEELS | ST235/85R16E | | |
| TONGUE JACK | 7K Drop Leg | | |
| HITCH | Standard 2-5/16" Ball, Optional 3" Pintle Eye | | |
| LIGHTS | LED / Incandescent | | |
| WIRING | Inside Conduits | | |
| PLUG | Standard 4 Prong Flat, Optional 7 Prong Flat RV | | |
| SAFETY CHAIN | 3/8" Grade 70 | | |
| STANDARD COLOR | Black Powder Coated, Other Colors Available | | |
| TILTING MECHANISM | Manual tilt with single snubber cylinder to cushion tilting of deck | | |
| SPARE TIRE WITH BRACKET | Standard | | |
| METAL FENDERS | Standard – Bolt On | | |
| TRACTION STRIPS | Deck mounted traction strips aid loading of small scissor lifts with small drive wheels | | |
| OPTIONS: | - Track Stop / Chains and Binders | | |
| GVWR (LBS) | GAWR (LBS) | WEIGHT (LBS) | CAPACITY (LBS) |
| 7,700 | 7,000 | 1,902 | 5,798 |

