

## STEELPOINT 5X10 – TANDEM AXLE

**E510H – HYDRAULIC**  
**E510E – ELECTRIC**

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

### TRAILER SPECIFICATIONS

|                         |  |
|-------------------------|--|
| DECK SIZE               | 61" Inside Fender X 120" Long. Overall 85" Wide X 17'6" Long |
| DECK                    | 1/8" Steel Diamond Plate                                     |
| DECK HEIGHT             | 19 1/2" Empty, 17 1/2" loaded                                |
| RAMPS                   | Spring Assisted Ramps  |
| TIE DOWNS               | 6 Each "D" Rings   |
| AXLES                   | 4.4K Torsion Hydraulic Axles                                 |
| BRAKES                  | Hydraulic / Electric   |
| SUSPENSION              | Torsion Axle   |
| TIRES AND WHEELS        | ST225/75R15  |
| TONGUE JACK             | 7K Drop Leg Side Wind  |
| HITCH                   | Standard 2" Ball, Optional 3" Pintle Eye                     |
| LIGHTS                  | LED / Incandescent   |
| WIRING                  | Inside Conduits  |
| PLUG                    | Standard 4 Prong Flat, Optional 7 Prong Flat RV              |
| SAFETY CHAIN            | 5/16" Grade 70   |
| STANDARD COLOR          | Black Powder Coated, Other Colors Available                  |
| SPRING ASSISTED RAMPS   | Standard   |
| SPARE TIRE WITH BRACKET | Standard   |
| PLASTIC FENDERS         | Standard   |
| OPTIONS:                | - Track Stop / Chains and Binders                            |

| GVWR (LBS) | GAWR (LBS) | WEIGHT (LBS) | CAPACITY (LBS) |
|------------|------------|--------------|----------------|
| 8000       | 2ea 4400   | 1840         | 6160           |

