

## STEELPOINT 6X10 – TANDEM AXLE

## U610LS – HYDRAULIC

All Steelpoint Trailers meet NATM and DOT Specifications.

All wear and replacement parts are bolted to the trailer frame for easy replacement including: Actuators, Tongue Jack, and Fenders.

### TRAILER SPECIFICATIONS

DECK SIZE	72" Inside Fender X 122" Long. Overall 99.5" Wide X 192" Long
DECK	1/8" Steel Diamond Plate
DECK HEIGHT	19 1/2" Empty, 17 1/2" loaded
RAMPS	Spring Assisted Ramps
TIE DOWNS	6 Each "D" Rings
AXLES	3.5K Spring Hydraulic Axles
BRAKES	Hydraulic
SUSPENSION	Springs
TIRES AND WHEELS	ST225/75R15
TONGUE JACK	7K Drop Leg Side Wind
HITCH	Standard 2" Ball
LIGHTS	LED / Incandescent
WIRING	Inside Conduits
PLUG	Standard 4 Prong Flat, Optional 7 Prong Flat RV
SAFETY CHAIN	5/16" Grade 70
STANDARD COLOR	Black Powder Coated, Other Colors Available
SPRING ASSISTED RAMPS	Standard
SPARE TIRE WITH BRACKET	Standard
PLASTIC FENDERS	Standard

GVWR (LBS)	GAWR (LBS)	WEIGHT (LBS)	CAPACITY (LBS)
6,500	2ea 3500	1,500	5,000

